

# KEL-JUMBO | Split cable entry frames

for cables with diameters of up to 65 mm / IP54 / UL Type 12



The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables. The innovative grommet design with the flex-membrane provides flexing and adjustment of the position for larger and more rigid cables.

We recommend round cut-outs, which can be made using standard knockout tools. Suggested cut-out: cable diameter +15 - 20%.

A flat rubber gasket is included in the shipment.




## Specifications


|                              |   |
|------------------------------|---|
| <b>IP rating (EN 60529)</b>  | IP54  |
| <b>UL Type (UL 50E)</b>      | UL Type 12  |
| <b>Material</b>              | Polyamide   |
| <b>Flame class</b>           | UL94-V0, self-extinguishing   |
| <b>Operating temperature</b> | -40 C° to 140 C°  |
| <b>Properties</b>            | vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free |
| <b>Mounting options</b>      | Screw type mounting   |
| <b>height</b>                | 35 mm   |


## Advantages & benefits

- Installation of cables up to 65 mm in diameter
- It is possible to install rigid cables at angles
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Strain relief according to EN 62444


## Product types & sizes

| KEL-JUMBO 1  | Part No.               | 42360         | Height                | 35 mm                                |
|--|------------------------|---------------|-----------------------|--------------------------------------|
|  | EAN                    | 4251269308550 | Mounting height       | 35 mm                                |
|  | Package quantity       | 1             | Cut-out size          | 78 x 80.5 mm                         |
|  | For max. no. of cables | 1             | No. of screw holes    | 4                                    |
|  | Max. cable diameter    | 65 mm         | Diam. of screw holes  | 7 mm                                 |
|  | Length                 | 110 mm        | Screw material        | Mild steel, galvanically zinc plated |
|  | Width                  | 116 mm        | Suitable for grommets | 1 x KTF                              |

| KEL-JUMBO 1 V2A  | Part No.               | 42360.200     | Height                | 35 mm                 |
|--|------------------------|---------------|-----------------------|-----------------------|
|  | EAN                    | 4251269308567 | Mounting height       | 35 mm                 |
|  | Package quantity       | 1             | Cut-out size          | 78 x 80.5 mm          |
|  | For max. no. of cables | 1             | No. of screw holes    | 4                     |
|  | Max. cable diameter    | 65 mm         | Diam. of screw holes  | 7 mm                  |
|  | Length                 | 110 mm        | Screw material        | Stainless steel (V2A) |
|  | Width                  | 116 mm        | Suitable for grommets | 1 x KTF               |

**KEL-JUMBO 2**

|                        |                      |                       |   |
|------------------------|----------------------|-----------------------|---|
| Part No.               | <b>42350</b>         | Height                | <b>35 mm</b>                                |
| EAN                    | <b>4251269308536</b> | Mounting height       | <b>35 mm</b>                                |
| Package quantity       | <b>1</b>             | Cut-out size          | <b>168 × 80.5 mm</b>                        |
| For max. no. of cables | <b>2</b>             | No. of screw holes    | <b>4</b>                                    |
| Max. cable diameter    | <b>65 mm</b>         | Diam. of screw holes  | <b>7 mm</b>                                 |
| Length                 | <b>200 mm</b>        | Screw material        | <b>Mild steel, galvanically zinc plated</b> |
| Width                  | <b>116 mm</b>        | Suitable for grommets | <b>2 x KTF</b>                              |

**KEL-JUMBO 2 V2A**

|                        |                      |                       |                              |
|------------------------|----------------------|-----------------------|------------------------------|
| Part No.               | <b>42350.200</b>     | Height                | <b>35 mm</b>                 |
| EAN                    | <b>4251269308543</b> | Mounting height       | <b>35 mm</b>                 |
| Package quantity       | <b>1</b>             | Cut-out size          | <b>168 × 80.5 mm</b>         |
| For max. no. of cables | <b>2</b>             | No. of screw holes    | <b>4</b>                     |
| Max. cable diameter    | <b>65 mm</b>         | Diam. of screw holes  | <b>7 mm</b>                  |
| Length                 | <b>200 mm</b>        | Screw material        | <b>Stainless steel (V2A)</b> |
| Width                  | <b>116 mm</b>        | Suitable for grommets | <b>2 x KTF</b>               |

**icotek**<sup>®</sup>  
smart cable management